

AGROFARM TB



DEUTZ-FAHR
415 - 425 TB



The technical specifications and images herein are purely indicative. DEUTZ-FAHR reserves the right to update this information at any time without notice.

Technical data		Agrofarm TB	
		415	425
ENGINE			
Emissions		Tier3	Tier3
Manufacturer		SDF	SDF
Cylinders/Displacement	n° / cm ³	4/4000	4/4000
Turbo Intercooler		●	●
Max. power (ECE R 120) @2000 rpm	kW / HP	70/95	78/106
Max. nominal power (ECE R 120) @2200 rpm	kW / HP	70/95	75/102
Max. torque @1600 rpm	Nm	373	390
Torque backup	%	21	23
Engine control electronic		●	●
Fuel tank capacity	litres	85	85
SHUTTLE			
Mechanical shuttle (LS)		●	●
Hydraulic power shuttle (GS)		○	○
Stop & Go system (GS)		○	○
MECHANICAL TRANSMISSION			
5-speed gearbox		●	●
Number of speeds	n°	10 + 10	10 + 10
Number of speeds with underdrive and creeper	n°	20 + 20	20 + 20
MECHANICAL TRANSMISSION WITH HI-LO (OPT)			
5-speed gearbox		●	●
Number of speeds	n°	20 + 20	20 + 20
Number of speeds with underdrive and creeper	n°	40 + 40	40 + 40
REAR PTO			
Electrohydraulic operation		●	●
540 PTO		○	○
540/540ECO PTO		●	●
540/540ECO/1000/1000ECO PTO		○	○
Ground speed PTO		○	○
FRONT AND REAR AXLE			
Electrohydraulically operated 4WD		●	●
Electrohydraulically operated differential locks		●	●
BRAKES AND STEERING			
4-wheel braking		●	●
Separate brakes valve		●	●
Independent Parking brake		●	●
Hydraulic trailer braking		○	○
Hydrostatic steering with independent pump		●	●
HITCH			
Mechanical rear hitch		●	●
Rear lifting capacity (std)	kg	3600	3600
Rear lifting capacity (opt)	kg	4500	4500
HYDRAULIC SYSTEM			
Pump flow rate	L / min	56	56
Open centre hydraulic system		●	●
Rear auxiliary spool valves	n° vie	4 / 6	4 / 6
PLATFORM			
Lateral transmission levers		●	●
Two pillard folding ROPS		●	●
Digital instrumentation		●	●
Driver's seat mechanical adjustment		●	●
DIMENSIONS AND WEIGHTS			
With rear tyres		420/70R24"	480/65R28"
Max. length without link arms	mm	4125	4125
Width min. / max.	mm	1939/2339	2101/2405
Ground clearance	mm	290	340
Wheelbase	mm	2400	2400
Front track min. / max.	mm	1374/1862	1588/1882
Rear track min. / max.	mm	1500/1900	1598/1902
Height at rear mudguards	mm	1314	1414
Max. weight with ROPS	kg	3200	3400
Maximum load capacity	kg	6200	6200

● STD ○ OPT

deutz-fahr.com



The use of original lubricants and coolants is recommended

DEUTZ-FAHR is a brand of SDF

