

# 4E Keyline SERIES.



4046E Keyline - 4050E Keyline  
4055E Keyline - 4060E Keyline




4E Keyline Series		4046E KEYLINE	4050E KEYLINE	4055E KEYLINE	4060E KEYLINE
<b>ENGINE</b>					
Emissions		Stage III A	Stage III A	Stage III A	Stage III A
Manufacturer		Simpson	SDF	SDF	SDF
Cylinders/Capacity	No./cm <sup>3</sup>	3/2700	3/3000	3/3000	3/3000
Aspiration		Natural	Natural	Turbo Intercooler	Turbo Intercooler
Max. & Rated power (ECE R120)	kW/hp	33/45	36.8/50	40.4/55	44.1/60
Rated engine speed	rpm	2200	2200	2200	2200
Max. torque	Nm	180	184	201	221
Mechanical engine control		●	●	●	●
Cooling liquid		●	●	●	●
Under-hood silencer with vertical exhaust		●	●	●	●
Fuel tank capacity	litres	55	55	55	55
<b>TRANSMISSION 1</b>					
Synchronised		○	○	○	○
Number of speed (with creeper)	n°	8+2 (12+3)	8+2 (12+3)	8+2 (12+3)	8+2 (12+3)
Minimum speed with reduction gear	km/h	0.5	0.5	0.5	0.5
Max. speed	km/h	34	34	34	34
Mechanical dry clutch		●	●	●	●
Waterproof seals		●	●	●	●
<b>TRANSMISSION 2</b>					
Synchronised		●	●	●	●
Number of speed (with creeper)	n°	8+8 (12+12)	8+8 (12+12)	8+8 (12+12)	8+8 (12+12)
Minimum speed with reduction gear	km/h	0.5	0.5	0.5	0.5
Max. speed	km/h	34	34	34	34
Mechanical dry clutch		●	●	●	●
Waterproof seals		●	●	●	●
<b>REAR PTO</b>					
Mechanical dry clutch		●	●	●	●
Mechanical engagement		●	●	●	●
PTO 540 / 540E / 540-1000		●/○/○	●/○/○	●/○/○	●/○/○
PTO 540 + reverse PTO		○	○	○	○
<b>FRONT AND REAR AXLE</b>					
Front wheel drive mechanically engaged (only 4WD versions)		●	●	●	●
Mechanically operated differential lock (rear/front)		●/-	●/-	●/-	●/●
Steering angle (2WD/4WD)	degrees/mm	55/51	55/51	55/51	55/51
<b>BRAKES</b>					
Girling braking system		●	●	●	●
Mechanical parking brake		●	●	●	●
<b>STEERING</b>					
Hydrostatic steering with independent pump		●	●	●	●
<b>HITCH</b>					
Category		II	II	II	II
Mechanical rear hitch with Easy Lift system		●	●	●	●
Rear hitch lift capacity	kg	1250	1600	1600	1600
<b>HYDRAULIC SYSTEM</b>					
Pump output (std)	l/min	27	31	31	31
Open-centre hydraulic system		●	●	●	●
Mechanical valve engagement		●	●	●	●
Rear hydraulic auxiliary valves	no. of ways	2/4	2/4	2/4	2/4
<b>DRIVING POSITION</b>					
Side control levers		●	●	●	●
2 post ROPS		○	○	○	○
Driver seat with mechanical suspension		○	○	○	○
Analogue instrumentation		●	●	●	●
<b>DIMENSIONS AND WEIGHTS</b>					
Rear tyres		16.9-28"	16.9-28"	16.9-28"	16.9-28"
Max. length	mm	3550	3550	3550	3550
Width (min.-max.)	mm	1800/1840	1800/1840	1800/1840	1800/1840
Wheelbase (4WD/2WD)	mm	1950/1920	1950/1920	1950/1920	1950/1920
Front track (4WD/2WD)	mm	1488/1462	1488/1462	1488/1462	1488/1462
Rear track	mm	1440	1440	1440	1440
Max. height at steering	mm	1634	1634	1634	1634
Weight with ROPS (4WD/2WD)	kg	2500/2100	2500/2100	2500/2100	2500/2100

● = standard ○ = optional - = not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

DEALER

To discover more please contact your dealer  
or visit [deutz-fahr.com](http://deutz-fahr.com).

DEUTZ-FAHR is a brand of  SDF

