

# // SERIES 5 KEYLINE

#### **UNMATCHED AGILITY**

Welcome to the world of the new DEUTZ-FAHR
Series 5 Keyline, an outstanding range of tractors that
embody versatility, modularity, strength and an enviable good
value for money ratio within the utility mid-basic segment.
The tractors in the Series 5 Keyline are designed to offer
maximum flexibility while ensuring reliable and innovative
performance. Agility is one of the distinctive features of these
tractors, thanks to a remarkable steering angle and cuttingedge solutions such as the PowerShuttle with adjustable
response, Stop&Go system, and ComfortClutch, which ensure
smooth and comfortable driving even in the most challenging
situations. Additionally, you can enhance the driving
experience with the optional Hi-Lo Powershift transmission,
allowing easy adaptation to different field requirements.

#### **OPTIMAL COMFORT**

Comfort is paramount in the new DEUTZ-FAHR Series 5 Keyline tractor models, ensuring optimal cab comfort through a range of features. The Hydro Silent-Blocks provide suspension into the cab, while the seats boast pneumatic suspensions for a smooth ride. Additionally, the fully adjustable steering column, both in height and depth, adds to the personalised comfort experience.

Inside the cab, convenience meets modernity with two USB ports, a practical smartphone holder, and an efficient air conditioning system. 12 work lights, ensuring excellent visibility even in low-light conditions.



The latest DEUTZ-FAHR Series 5 Keyline.

CONFIGURABILITY AT ITS FINEST.





#### **LEADING EFFICIENCY AND SAFETY**

The new DEUTZ-FAHR Series 5 Keyline tractor models enhance efficiency and productivity in all agricultural activities. The models in the Series 5 Keyline boast a maximum road speed of 40 km/h, achievable at a low and economical engine speed, ensuring excellent efficiency during transfers. Moreover, the Powershift Hi-Lo transmission provides a range of speeds suitable for every need, while wet disc brakes on all four wheels ensure effective safety during operation. Finally, the electro-hydraulic activation of the PTO allows precise control of equipment, further enhancing the efficiency of agricultural operations.

#### **EXCEPTIONAL VERSATILITY**

The new models showcase remarkable versatility in the agricultural machinery sector. This versatility begins from the heart of the tractor, where the sophisticated FARMotion 45 Stage V engine operates with or without AdBlue. The transmission, capable of reaching up to 40+40 speeds, ensures the right gear for any task. Furthermore, the Series 5 Keyline tractor is equipped with a powerful hydraulic system and is ready to be fitted with the Ready Kit, an essential optional for activities requiring a front loader. With these features, the 5 Keyline sets a new standard for versatility in the agricultural sector, adapting to a wide range of challenging tasks and needs.



The new DEUTZ-FAHR Series 5 Keyline tractor models stands out for its exceptional configurability, adapting to the most demanding needs. The Series 5 Keyline Series is suitable for a wide range of activities, including field work, row crop cultivation, hay-making activities, stationary tasks, and operations with a front loader. Its outstanding versatility is due to the electro-hydraulic engagement of the 4 wheel drive and the PTO, and the groundspeed PTO with an independent shaft. Additionally, the powerful hydraulic system with a maximum of 6 rear ways, the 2 stage Powershift transmission with Hi-Lo, and a choice of creeper gears expand the range of configurations. User can memorise up to 2 engine speeds which can be set and recalled. Along with a wide range of tyres offering generous ground clearance, enable efficient and comfortable performance of all types of activities.

# // VERSATIL

Introducing the new DEUTZ-FAHR
Series 5 Keyline: ideal for a multitude of applications.



## **// ENGINE**

### Tailored specifically for agriculture.

The new FARMotion engine family is meeting Stage V emissions regulations and is exceptionally compact. This allows for a streamlined, sloped cowl design on the tractor, ensuring excellent visibility from the driver's seat and enabling generous steering angles. Equipped with the 4-cylinder FARMotion 45 engines, the new DEUTZ-FAHR Series 5 Keyline offers outstanding manoeuvrability and robust pulling power. Ready for the future, they are also HVO certified.

#### **Efficiency**

The Common Rail fuel injection system, capable of reaching injection pressures up to 2000 bar and managed entirely electronically, enhances combustion by ensuring more efficient fuel atomisation. This results in significant reductions in fuel consumption, noise, and emissions. Additionally, the high injection pressures enable the engine to respond swiftly to sudden, substantial changes in load. A dedicated electronic control unit optimises fuel delivery in real-time based on engine speed and load, with a speed management function allowing operators to set and recall specific engine speed limits for various tasks or maintain a consistent engine speed.

#### **Outstanding performance**

These engines respond promptly to changes in load and deliver more usable performance even at lower engine speeds, thanks to enhanced torque and power curves. The flagship model, the 5105 Plus, boasts a maximum power of 106 HP and an impressive torque of 433 Nm.

#### **HIGHLIGHTS**

- 75 HP version available without the need for AdBlue
- Electronic Common Rail high-pressure injection system
- Two user-settable engine speed memories
- Simple maintenance



FARMotion 45 engine with power ratings from 75 to 106 HP with or without SCR.



## // TRANSMISSION AND PTO

### Unmatched configurability.

The new DEUTZ-FAHR Series 5 Keyline tractor models stand out for its exceptional configurability, adapting to even the most demanding needs. All variants of the transmission in the new DEUTZ-FAHR Series 5 Keyline feature a 5-speed gearbox, offering multiple configuration possibilities to meet every specific requirement. The choice between a synchronised

mechanical reverser shuttle or a hydraulic PowerShuttle with 2-stage Powershift provides further customisation options. All versions reach a maximum speed of 40 km/h at reduced engine speeds. The creeper adds flexibility, doubling the number of gears in both forward and reverse, allowing the tractor to move at speeds lower than 400m/h with the



> Mechanical shuttle with ergonomic lever on steering column.

> PowerShuttle with SenseClutch 5-levels adjustment and Stop&Go function.




#### **HIGHLIGHTS**

- 5-speed main transmission with up to four ranges
- 2-steps Powershift with Hi-Lo
- PowerShuttle with adjustable response and Stop&Go
- ComfortClutch function enables clutch free gear changes

engine at maximum rated speed (depending on tyre size). A key feature of the PowerShuttle is the renowned Stop&Go function, allowing the tractor to be stopped without using the clutch. The PTO is controlled by a multiple wet-disc clutch and is operated electro-hydraulically by simply pressing a button. PTO controls on the rear fenders improve comfort

when using equipment. The PTO is equipped with different speeds to ensure the right power for the implements, and the groundspeed PTO is equipped with a dedicated shaft for precise control.




# // HYDRAULIC SYSTEM AND LIFTS

Top-notch performance and remarkable adaptability.

The new DEUTZ-FAHR Series 5 Keyline tractor model is equipped with a powerful hydraulic system and a sturdy rear lift, ensuring high-performance capabilities in every task. The hydraulic system has a capacity of 55 l/min, while the steering has an independent pump of 35 l/min. There are 2 rear double-acting hydraulic spool valves with mechanical control, featuring flow and free return regulators, with an option for 3 rear spool valves available as an optional extra. These distributors come with a "detent" function for the mechanical control lever, ensuring continuous oil flow. The robust rear lift, is renowned for its exceptional precision and efficiency, offering unparalleled performance. As standard, the new DEUTZ-FAHR Series 5 Keyline is equipped with the proven rear lift with mechanical control, with the additional option of EasyLift for increased convenience, allowing for easy lifting and lowering of the rear lift with a single touch. The technical specifications are outstanding, with a maximum capacity of up to 4525 kg and a category II 3-point hitch. The rear lift is the faithful ally for demanding tasks.





> Up to 3 rear hydraulic valves.

> Everything in reach thanks to the ergonomic and organised side console.

## **HIGHLIGHTS**

- Up to 6 rear hydraulic valves
  55 l/min hydraulic system
  Independent steering pump with up to 35 l/min
  4525 kg maximum lift capacity





> External control for rear lift.

# // TOPVISION<sup>evo</sup>

# The cab you've been searching for, with just 4 pillars.

The new DEUTZ-FAHR Series 5 Keyline tractor model is equipped with a comfortable cab. One significant feature of the DEUTZ-FAHR 5 Keyline cab is its construction with only 4 pillars, making it comfortable and practical. The cab boasts an advanced and modern design, with its spacious window and eye-catching profile of the monolithic hood ensuring fantastic visibility in all conditions. Even in low-light conditions, visibility remains perfect, thanks to the 12 powerful work lights supporting every activity.

The new TopVision<sup>evo</sup> cab is always suspended on Hydro Silent-Blocks, which ensuring excellent comfort by reducing vibrations by up to 40%. The telescopic and fully adjustable steering column, along with the suspended seat with multiple adjustments, allows operators of any height to find their perfect position for field and road transport activities. For additional comfort, the radio is included as standard.

Low noise levels and intuitively organised instrumentation controls create an impeccably comfortable working environment. Among the cab customisation options are a factory-mounted bracket for mounting a monitor or additional devices for equipment control. There is a passenger seat, multiple electrical outlets, and 2 USB ports; convenient smartphone and cup holders.

The opening roof and rear window ensure excellent cab ventilation. The air conditioning system guarantees cab comfort throughout all seasons. 10 ventilation outlets provide purified air throughout the cab via specific filters and maintain a pleasant internal climate.

## HIGHLIGHTS

- > High visibility with 4 pillar cab
- > More comfort with Hydro Silent-Block suspension
- > 2 cab configurations: Comfort cab and Hi-Line cab
- > FOPS-compliant roof with roller sun screen
- > Air conditioning as standard
- > 2 seat configurations: mechanical suspension or air-suspension



> 4 pillar cab for higher visibility.





> Radio included as standard.

> Powerful air conditioning system included as standard.

# // FRONT LOADER

## All the strength for the DEUTZ-FAHR Series 5 Keyline.

The new DEUTZ-FAHR Series 5 Keyline tractor has been designed with a particular focus on its versatility, thanks to the implementation of a state-of-the-art front loader. This fundamental component is available in two variants: the Light Kit and the Ready Kit, both installed directly at the factory to ensure optimal performance from the first use.

Both kits are equipped with a special frame designed for front loader mounting. However, the Ready Kit offers an additional advantage with the inclusion of a strategically positioned Joystick next to the driver, complete with all necessary connections for convenient and safe operation.

To ensure a balanced distribution of weight between the front and rear axles, dedicated rear wheel weights are available. This not only reduces the load on the front axle but also prevents excessive mechanical stresses, ensuring greater durability and reliability over time.

The two front loader models, the Solid and the Profiline, offer mechanical parallel control with Z kinematics, as well as tipping, quick dump, and return to level (RTL) functions. These features allow for considerable time savings during daily operations.

The design of the loader arms, with integrated control rods and a flat cross tube, ensures excellent front visibility. Additionally, internal hydraulic passages contribute to protecting hydraulic lines and give the loader a compact and tidy appearance.

To further increase the capacity and productivity of the front loader, the DEUTZ-FAHR Series 5 Keyline offers a hydraulic PowerShuttle with smooth response, featuring 5 different levels of reactivity. The Stop&Go function allows the driver to stop and restart the tractor using only the brake pedals, without having to engage the clutch.

Finally, the high-visibility roof, compliant with FOPS regulations, represents an additional safety and comfort feature during the use of the front loader, ensuring adequate operator protection.





loader





# // WORK LIGHTS

A new lighting package for effective night work.

These tractors offer several configurations in terms of exterior lighting, allowing operators to customise their machines to suit their work needs precisely.



Front headlights



Support for monitor or other additional device for equipment control.

## // OPTIONAL EQUIPMENT

### Everything you need.

The new DEUTZ-FAHR Series 5 Keyline tractor is designed to offer tailor-made customisations, providing operators with the opportunity to adapt the machine to their specific needs with a wide range of accessories and configuration options.

The numerous available options allow for complete customisation of the tractor. Among these options are various types of trailer braking systems, both hydraulic and pneumatic, making the new DEUTZ-FAHR Series 5 Keyline suitable for heavy-duty road transport as well.

In addition, there are numerous configuration options, including a wide range of wheels with a choice between fixed or adjustable track width rims. Furthermore, there are many variants of approved tyres, ideal for all types of activities and to ensure optimal comfort both in the field and on the road. Operators can further customise the tractor by choosing from various configurations of front and rear mudguard configurations, as well as front and rear monolithic and suitcase ballast weights, and ring ballast weights for the rear wheels. As an option, there is also a compressor with 3 quick connectors (2 external and one in the cab).






> External and in-cab air connections for air-compressor accessories.

> Smartphone holder with USB socket.

/							
		SERIES 5 KEYLINE					
TECHNICAL DATA	-	5075 5095 5105			5105 PLUS		
		50/5	5095	5105	3 103 PLU3		
ENGINE Model			FARM	45			
			FARMot				
Emission level	0/	Stage V					
Cylinders/Displacement	n°/cc	4/3849 103/115.5					
Bore/Stroke	mm						
Turbo Intercooler	bar	2000					
Common Rail injection	kW/HP	2000 55.4/75 70/95 78/106					
Max. power (ECE R120)  Power at rated engine speed (ECE R120)	kW/HP	54.8/74 66.4/90 74/101					
9 1 , ,	Nm	359 389 433					
Max. torque Engine speed at maximum torque	Nm	359 389 433 1400					
Electronic engine control	INIII	1400 •					
PowerCore air filter		•					
Fuel tank capacity		145					
AdBlue tank capacity		- 10					
EAT	System	DOC+DPF DOC+DPF+SCR					
TRANSMISSION	System	БОСТЫТ		DOCTOTTISCK			
SDF transmission	Туре		T4330		T4350		
Gearbox	n°	5 gears x 2 or 4 ranges					
MECHANICAL SHUTTLE		_	J gcdi3 x Z v	or 4 runges			
Shuttle	Туре		Mechanical with lever	under steering whe	el		
N° of speed (4 ranges)	n°	Mechanical with lever under steering wheel 20+20					
N° of speed with Hi-Lo (2 ranges)	n°	20+20 Hi-Lo					
N° of speed with Hi-Lo (4 ranges)	n°	40+40 Hi-Lo					
POWERSHUTTLE			10110	20			
PowerShuttle	Туре	Hydraulic with lever under steering wheel					
Adjust. Response of PowerShuttle	.,,,,,	5 different setting					
N° of speed (4 ranges)	n°	20+20					
N° of speed with Hi-Lo (2 ranges)	n°	20+20 Hi-Lo					
N° of speed with Hi-Lo (4 ranges)	n°	40+40 Hi-Lo					
Stop&Go		•					
ComfortClutch		•					
PTO							
Electrohydraulic engagement			•	)			
540/540ECO			•				
540/1000*			C	)			
LIFT							
Mechanical rear lift			•	)			
Mechanical rear lift with EasyLift		0					
Rear lifting capacity (STD)	kg	3600					
Rear lifting capacity (OPT)	kg	4525					
HYDRAULICS							
Pump flow	l/min	55					
Rear spool valves	n°	2/3					
BRAKES							
4 wheel braking			•				
Mechanical parking brake		•					
Hydraulic trailer brake		0					
Pneumatic trailer brake			C	)			
FRONT AXLE							
Front axle	Size		1.5		2		
Steering angle	degrees	50 55					
Electrohydraulic 4WD engagement			•				
Electrohydraulic Diff Lock engagement				)			
CAB							
4 pillar cab							
Standard roof		•					
High visibility roof - FOPS		0					
Hydro Silent-Block suspension		•					
Manual A/C		•					
Mechanical suspended seat		•					
Pneumatic suspended seat		0					
Passenger seat		0					
External controls for PTO and lift		0					
Radio		•					

 $<sup>\</sup>bullet =$  standard  $\bigcirc =$  option - = not available





TECHNICAL DATA		SERIES 5 KEYLINE				
		5075	5095	5105	5105 PLUS	
DIMENSIONS AND WEIGHTS						
With front tyre	Size	380/85 R24			420/85 R24	
With rear tyre	Size	420/85 R34			460/85 R34	
Wheelbase (A)	mm					
Max. length (B)	mm	4268				
Total height (C)	mm	2718			2743	
Width (D)	mm	2051			2205	
Centre rear axle – cab	mm	1968				
Weight	kg	4000			4250	
Front admissible load	kg	2900			3000	
Rear admissible load	kg		3700		4000	
Total admissible load	kg		6500		7000	

<sup>\*</sup> via dealer

Technical data and figures are only provided for guidance. DEUTZ-FAHR is committed to continuously adapting its products to your requirements and therefore reserves the right to make updates without prior notice.



