

TECHNICAL DATA 8280 W Mark Widdai W7 Model Control W7 Market Control W7 Model Science M1 Control W7 Market M2 Sold Market M2 Sold Market M2 Sold Market M3 Market M3 Market M3 Market M3 <th></th> <th></th> <th></th>			
niciticImage: second secon			8280 W
NodeConstrainedConstrainedCylinder OrbigaronmetCylinder OrbigaronmetCylinder OrbigaronmetCylinder OrbigaronmetSeeConstrained APersonal ConstrainedSeeConstrained AName See See See See See See See See See S	TECHNICAL DATA		8280 W
Finished Context (Context)Tridectage with days at costs••Tridectage with days at costs••Revealts costsfigs••Revealts costsfigs•CostsRevealts costsfigsCostsRevealtsRevealts costsfigsCostsRevealtsRevealts costsfigsCostsRevealtsRevealts costsfigsRevealtsRevealtsRevealts costsfigsRevealtsRevealtsRevealts costsfigsRevealtsRevealtsSpeed at narrown torgafigsRevealtsRevealtsRevealts costsrevealtsRevealtsRevealtsRevealts RevealtsrevealtsRevealtsRevealtsRevealts RevealtsrevealtsRevealtsRe			
Cyndrafian (Caling air colingr/*0Revenable costing famIP0Revenable costing famIP0Max prover (CA 12D)WVI P202073Max right specific (Grad)Mm100Max right specific (Grad)Mm100Max right specific (Grad)Mm100Max right specific (Grad)Mm100Max right specific (Grad)Mm100Ar filter specific (Grad)Mm100Post Specifi	1		
Trobusiness			
Revenue of CS 170)VisitGeneration billMax proy (CS 170)W/HGeneration billMax segior production of the sector o		nº/cc	
linkcionTypeCommon hallMax. steps speed (nated)Nam.Regress speed (nated)Nam.Max. steps speed (nated)Nam.Regress speed (nated)Nam.Steps speed (nated)Nam.Regress speed (nated)Regress speed (nated)Step at name name name name name name name name			
Mox. regins groups (CE 8120)UV/P202075Mox. regins groups (Erstein)Im20203Mox. regins groups (Erstein)Im20203Speed at maximum torqueIm1mAller with displot?Im3mSpeed at maximum torqueIm3mAller with displot?Im3mTotal at copicityIm2mModiIm2m2mModiIm2m2mModiIm3m3mTotal at copicityIm3m3mModiIm <t< td=""><td></td><td>T</td><td>-</td></t<>		T	-
Max. targe speel (rate)rpm2200Nac. targeNm186Targe rie%36Speel at nationatoquerpm350At files with dat better••TALLSSON••TALLSSON•2717305Rower Status••Rower Status••	-		
Max maxNm186Greer Arm andmum tropu%36Speed at maximum tropu%36Affler vith durit diptorRuit an cognation tropu10520Prest shart diptor-217300ModelCarlowRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttMainum speednhMainum speedInninHarthwarttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowersharttRowershartt			
Trengenine%36Speed transimu torqueym10500Arffler with dati sjectorTALMESTONISpeed transimu torqueTALMESTONISpeed transimu torqueTALMESTONISpeed transimu torqueRowell stateISpeed transimu torqueRowell stateISpeed transimu torqueRowell stateISpeed transimu torqueRowell stateISpeed transit stateRowell stateISpeed transit stateRowell stateIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	o i i i j		
Speed and angebasepm1500Ariller with digital•Pail and capacity•Model2027 17300Model••Rowsfastit••Rowsfastit••Rowsfastit••Rowsfastit••Rowsfastit••Rowsfastit••Rowsfastit••Rowsfastit••Rowsfastit••Rowsfastit••Mainuan geed••Mainuan geed••Hannan geed•<	•		
Air filter with data griederIIFachard accountIS20TAXNETSIONIZ177300Rever ShattleIICondroxn"Geners 14 Rowershift steps and CreagerIRower ShattleIICondrox Lift Rowershift steps and CreagerIICondrox Lift Rowershift steps and CreagerIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII		rpm	1500
TAXMONIONUZTT7300Power Shittis••Power Shittis••Carloan*6 gears + 4 Powerhittistaps.Krist Sage and Leaguer4 0 + 40ControtClutchIm•Makrum speed.km/h4 0 + 20ControtClutchIm0.48Makrum speed.km/h0.48Makrum speed.Im0.48Makrum speed.Im•Pomp flowImImMichael Statistic Barrow••Spool values controlsTypeImPomp flowIm•Pomp flowIm•Pomp flow flow controlsTypeImPomp flow flow controlsTypeImPome flow flow controlsType <td></td> <td>·</td> <td>•</td>		·	•
NodeZZPowsflattin••Caraboxn°§gars A Powerhift steps and Creager*N° of speat with A Powerhift steps and Creager*•N° of speat with A Powerhift steps and Creager%nh•N° of speat with A Powerhift steps and Creager%nh•Maximum speedkmh••Minnum speedkmh••Nord Speat Steps and Step a	Fuel tank capacity	l	520
provesting typeImage: Construction of the second of type of the second of type of typ	TRANSMISSION		
DVMSSNIFTCardoxn°6 genx A Pownhit steps and CreeperN° of spenx A Pownhit steps and Creeper9 40Controt.Cluch4 0Mainum spendkm/h40 ECOMinimum spendkm/h40 ECOMinimum spendkm/h40 ECOMinimum spendm/h40 ECOMinimum spend116 ESMore Science	Model		ZF T7300
Candoxn°6 gas 4 0 4 40N° di speci Mi taya and Creper40 4 40Condro CluchN0Maximum specikm/h0.620Maximum specikm/h0.820HOPALLES AND LINKAGEV0.48HOPALLES AND LINKAGEV0.820HOPALLES AND LINKAGEV0.820HOPAL BURGER AND LINKAGER AND LINKAGERV0.820HOPAL BURGER AND LINKAGER AN			•
N° of geod with 4 Powerlin taspa and CreegerIMaximum speedkm/h40 ECOMaximum speedkm/h40 ECOMaximum speedkm/h0.48Information speedinformation speed116 LSMaximum speedN°116 LSMaximum speedinformation speedinformation speedSpoot statistic pumpinformation speedinformation speedSpoot statistic pumpinformat			
ControllaciónImpImpMaximum spedkm/n4DECOMinimum spedkm/n4DECOMinimum spedl/min11615Indepandent stering pumpImpImpSpolu vives controlsTypeMechanicalSpolu vives controlsn*MechanicalMyriadica auxiliary control vivesn*MechanicalMyriadica couplent)ImpMechanicalBerron insign fining capacityn*MechanicalPorron linkage filting capacityKgStoresFront linkage filting capacityKgStoresRar Mich 201000KgStoresRar Mich 201000ImpStoresRar Mich 201000ImpStoresRar Mich 201000ImpImpRar Mich 201000 <td></td> <td>n°</td> <td></td>		n°	
maximum speedimm40 (COHinimum speedkm/m0.48Hinimum speed(/min10.10Hiniba LinkAcie••Pum flow(/min•Spool values controlsType•Hydradia casaling control valuesn*•Power Boyond (tandard couplers)I•Electronic ran (fin••Rear Inlage lifting capacityKg•Foot Inlage lifting			
Minimu speedInth0.48HYR28LUESAND LINKAGEVirin116 LSHyrR28LUESAND LINKAGEVirin116 LSIndependent stering pump••Solo Vakes ControlsTypeMethanicalHyrRaf Laxilling control vakesn*•HyrRaf Laxilling control vakesn*•Power Bayond (transd couplers)LG•Electronic rear lift-•Fore linkage lifting capacityKg•Fore linkage lifting capacityKg•Rar PTO SoftCO/1000LG•Rar PTO SoftCo/1000LG•SoftCo/1000LG•SoftCo/1000LG•SoftCo/1000LG•SoftCo/1000LG•SoftC		km/h	-
Integrander Vini This Pump flow 1016 IS Independent steering pump • Spool vives controls Type Mechanical • Mybaulic Auxiliary control valves n° Power Boyend (tandard couplers) E Electronic rear III • Rear Intage III'ing capacity Kg Electronic rear III • Front Linkage III'ing capacity Kg Front III'Age III'Ing Capacity Kg Rear PIO 400 • ANLE AND BRACES • Model DANA M60HD Electro-Indytraulic differential lock 100% and 4VD • ASteering angle degrees Steering angle degrees Steering angle degrees			
Pump flow Independent stering pumpImage and the stering pumpSpool valves controlsTypeMydraulic auxiliary control valvesn"Mydraulic auxiliary control valvesn"Byours Byond (tankard couplers)KgBert indeg (filing capacityKgBar indeg (filing capacityKgBar indeg (filing capacityKgFront Inkage (filing capacityKgFront Inkage (filing capacityKgFront Inkage (filing capacityKgBar PIO 540ECO/1000KgRer Aufo PTOKgRer PIO 540ECO/1000KgRer Aufo PTOCRer PIO 540ECO/1000KgRer Aufo PTOCRer Aufo PTOCRer PIO 540ECO/1000KgRer Aufo PTOCRer Aufo PTOCStering angleGStering angleGAufon CapacityCCabCCabCStering angle Prove PTOCSter Machrone Prove PTOCCabCCabCCabCSter Machrone PTOCCabCCabCCabCSter Machrone PTOCCab<		N11/11	0.40
Independent stering pumpImage: Image: Im		l/min	116 LS
Spok laws controlsTypeMechanicalHydraulic auxiliary control valvesn°4Hydraulic auxiliary control valvesn°4Hydraulic auxiliary control valvesn°4Electronic rear liftn0Bear linkage lifting capacityKg10500External operation on rear findersn0Front linkage lifting capacityKg5100Rear P10 VoltoKg0Rear P10 VoltoN0Rear P10 VoltoN0Rear P10 Volto movable shaft100Rear P10 Volto movable shaft100Rotte SAND BRAKES00ModelM00Steering angledegree55Nechanical parking brake00Cob1000Steering angledegree55Nechanical parking brake00Cob1000Astity Stepping100Astity Stepping	•	(, min	
hydaulic auxilary control valvesn"4Power Beyond (standar couplers)IRear inkage litting capacityKgRear inkage litting capacityKgTorot linkage litting capacityKgFront linkage litting capacityKgFront linkage litting capacityKgRear Atto PTOKgRear Atto PTOCRear Atto PTOCAtti SystemCAtti SystemCAtti SystemCSteering angledegreesSteering angleGegreesCabCAtti SystemCSteering angleCAtti SystemCSteering angleGegreesCabCAtti SystemCSteering angleGegreesCabCAtti SystemCSteering angleGegreesCabCAtti SystemGegreesSteering angle		Туре	Mechanical
Electonic rear liftMgImage of the second seco			4
Rear Intinge parting capacityKg10500Externat operation on rear fenders•Front linkage lifting capacitykg•Front linkage lifting capacitykg•Store TO•••Rear PTO stoRCC/1000•••Rear PTO three movable shaft•••Rear PTO store movable shaft•••Rear Store movable shaft• <td></td> <td></td> <td>•</td>			•
Extension orear fendersImageImageFront linkageKg5100PTOFor linkage5100PTOImageS100PTOImageImageRear PTO SAGECO/1000ImageImageRear PTO With removable shaftImageImageFord IF TO 1000ImageImageAXES SAND BRAKESImageImageAvect SAND BRAKESImageImageSteering angledegreesS5ModelImageImageSteering angledegreesS5Mechanical parking brakeImageImageCabImageImageCabImageImageSteering angleImageImageAdvance digital displayImageImageSteering angleImageImageCabImageImageCabImageImageSteering angleImageImageCabImageImageCabImageImageCabImageImageCabImageImageSteering angleImageImageCabImageImageCabImageImageSteering angleImageImageCabImageImageCabImageImageCabImageImageCabImageImageSteering angleImageImageSteering angleImageImageSteering angle	Electronic rear lift		•
Front linkageMMFront linkageMS100Front linkageMS100PoImage: State	Rear linkage lifting capacity	Kg	10500
Front linkage illiting capacityKg5100PTOProProRear PTO 50ECO/1000Rear PTO twith removable shaftGent PTO 1000AXLES AND BRAKESTotoldAXLES AND BRAKESSteering angleGent PTO SystemGent PTO SystemSteering angledegreesSteering angleMechanical parking brakeCabCabSteering angleMax-Professional Plus, pneumatic suspension and swivelPassenger seatAvance digital displayLED dvining lightsLED dvining lightsSteering angleMax-Professional Plus, pneumatic suspension and swivelPassenger seatAvance digital displayLED dvining lightsLED dvining lightsSteering angleMiteNEDNEXPostenstonMiteNEDNEXDIMENSIONS AND WEICHTSFront Tyres (min.)mmRear Tyres (min.)mmMitenskammAriage and the displayUrest (min.)mmAriage and the displayUrest (min.)mmAriage and the displayUrage and the displayDifferent and the displayDifferent and the display	External operation on rear fenders		
PTO C Rear Pto 540ECO/1000 ● ●			-
Rear PTO 540ECO/1000IndexRear Atto PTOIndexRear PTO with removable shaftIndexFront PTO 1000IndexAxLES AND BRAKESIndexModelIndexElectro-hydraulic differential lock 100% and 4WDIndexElectro-hydraulic differential lock 100% and 4WDIndexCabIndexIndexCabIndexIndexSilent-Block cab suspensionIndexAlvance digital displayIndexEle driving lightsIndexIED driving lightsIndexIED driving lightsIndexIED driving lightIndexIEnd frin,IndexMeelbaseIndexIength (ini)IndexHeight (max)IndexVidel (max)IndexInt differential (ini)IndexHeight (max)IndexIength (inini)IndexHeight (max)<		Kg	5100
Rear Auto PTOImage: Constraint of the monoble shaftImage: Constraint of the monoble shaftRear PTO with removable shaftImage: Constraint of the monoble shaftImage: Constraint of the monoble shaftFont PTO 1000Image: Constraint of the monoble shaftImage: Constraint of the monoble shaftAXES AND BRAKESImage: Constraint of the monoble shaftImage: Constraint of the monoble shaftModelImage: Constraint of the monoble shaftImage: Constraint of the monoble shaftElectro-hydraulic differential lock 100% and 4WDImage: Constraint of the monoble shaftElectro-hydraulic differential lock 100% and 4WDImage: Constraint of the monoble shaftElectro-hydraulic differential lock 100% and 4WDImage: Constraint of the monoble shaftElectro-hydraulic differential lock 100% and 4WDImage: Constraint of the monoble shaftElectro-hydraulic differential lock 100% and 4WDImage: Constraint of the monoble shaftElectro-hydraulic differential lock 100% and 4WDImage: Constraint of the monoble shaftCabElectro-hydraulic differential lock 100% and 4WDCabImage: Constraint of the monoble shaftCabImage: Constraint of the monoble shaftSett Max-Profesional Plus pneumatic suspension and swivelImage: Constraint of the monoble shaftPasenger seatImage: Constraint of the monoble shaftAdvance digital displayImage: Constraint of the monoble shaftED diving lightImage: Constraint of the monoble shaftDIMENCISTENTImage: Constraint of the monoble shaftElect the monoble shaftImage: Constraint of the m			•
Rear PTO vith removable shaftImage: constraint of the state			
Front PTO 1000OOAXLES AND BRAKESModelDANA M60HDElectro-lydraulic differential lock 100% and 4WDAASM systemdegreesSteering angledegreesMechanical parking brakedegreesCABGCABGSilent-Block cab suspensionGAir conditioningGSee Max-Professional Plus, pneumatic suspension and swivelGPassenger seatGAdvance digital displayGLED driving lightsGDirthersONS AND WEIGHTSGFront tyres (min.)MRear tyres (min.)MRear tyres (min.)MMeebaseMmGround clearancemmGround clearancemmGround clearancemmMeaduleKgMeaduleKgMaximum permissible axle load, frontKgMaximum permissible axle load, frearKgMaximum permissible axle load, frearKgMaximum permissible axle load, frearKg			
AXLES AND BRAKES Model Image: Constraint of the second of the			-
ModelImage: Constraint of the second sec			
ASM systemImage: Arrow of the systemSteering angledegreesSteering angle parking brakedegreesMechanical parking brakedegreesCabImage: Arrow of the systemCabImage: Arrow of the systemSilent-Block cab suspensionImage: Arrow of the systemAir conditioningImage: Arrow of the systemSeat Max-Professional Plus, pneumatic suspension and swivelImage: Arrow of the systemPassenger seatImage: Arrow of the systemAdvance digital displayImage: Arrow of the systemLED working lightsImage: Arrow of the systemDIMENSIONS AND WEICHTSImage: Arrow of the systemFront tyres (min.)Image: Arrow of the systemRear tyres (min.)Image: Arrow of the systemWheelbaseImage: Arrow of the systemVidth (max.)Image: Arrow of the systemGround clearanceImage: Arrow of the systemVidth (max.)Image: Arrow of the systemTotal uladen weightKgMaximum permissible axle load, rearKgMaximum permissible axle load, rearKg			DANA M60HD
Steering angledegrees55Mechanical parking brakeIICAbCABCABCabIISilent-Block cab suspensionIIAir conditioningIISeat Max-Professional Plus, pneumatic suspension and swivelIIPassenger seatIIAdvance digital displayIILED working lightsIIDMENSIONS AND WEIGHTSIIFront tyres (min.)IIRear tyres (min.)ImIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	Electro-hydraulic differential lock 100% and 4WD		•
Mechanical parking brakeCCABCabSilent-Block cab suspensionAir conditioningSeat Max-Professional Plus, pneumatic suspension and swivelPassenger seatAdvance digital displayLED working lightsLED driving lightsDIMENSIONS AND WEIGHTSFront tyres (min.)Rear tyres (min.)mmRear tyres (min.)mmHeight (max.)mmHeight (max.)mmVidth (max.)mmCarancemmCond clearancemmTotal unladen weightKgMaximum permissible axle load, frontKgMaximum permissible axle load, frontKgMaximum permissible axle load, rearKgMaximum permissible axle load, rearKg	ASM system		•
CABCabImage: Colspan="2">Colspan="2" <colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2">Colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2< td=""><td>Steering angle</td><td>degrees</td><td>55</td></colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2<></colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"<colspan="2"></colspan="2"<colspan="2"<colspan="2"></colspan="2"<colspan="2"></colspan="2"<colspan="2"></colspan="2"<colspan="2"<colspan="2"></colspan="2"<colspan="2"<colspan="2"></colspan="2"<colspan="2"></colspan="2"<colspan="2"></colspan="2"<colspan="2"></colspan="2"></colspan="2"></colspan="2"></colspan="2"></colspan="2"></colspan="2"></colspan="2"></colspan="2"></colspan="2"></colspan="2"></colspan="2">	Steering angle	degrees	55
CabGeGeSilent-Block cab suspensionIIAir conditioningIISeat Max-Professional Plus, pneumatic suspension and swivelIIPassenger seatIIAdvance digital displayIILED working lightsIIDIMENSIONS AND VEICHTSIIFront tyres (min.)MmIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	Mechanical parking brake		•
Silent-Block cab suspensionImage: Silent-Block cab suspensionAir conditioningImage: Silent-Block cab suspension and swivelImage: Silent-Block cab suspension and swivelSeat Max-Professional Plus, pneumatic suspension and swivelImage: Silent-Block cab suspensionPassenger seatImage: Silent-Block cab suspensionAdvance digital displayImage: Silent-Block cab suspensionLED working lightImage: Silent-Block cab suspensionDIMENSIONS AND WEIGHTSImage: Silent-Block cab suspensionFront tyres (min.)Image: Silent-Block cab suspensionRear tyres (min.)Image: Silent-Block cab suspensionWheelbaseImage: Silent-Block cab suspensionLength (min.)Image: Silent-Block cab suspensionHeight (max.)Image: Silent-Block cab suspensionGround clearanceImage: Sile axle load, frontMaximum permissible axle load, frontKgMaximum permissible axle load, rearKg			
Air conditioningImage: ConditioningSeat Max-Professional Plus, pneumatic suspension and swivelImage: ConditioningPassenger seatImage: ConditioningAdvance digital displayImage: ConditioningAdvance digital displayImage: ConditioningLED working lightsImage: ConditioningLED working lightsImage: ConditioningCondetSord SAMD WEIGHTSImage: ConditioningFront tyres (min.)Image: ConditioningMetelbaseImage: ConditioningNetelbaseImage: ConditioningLength (min.)Image: ConditioningHeight (max.)Image: ConditioningGround clearanceImage: ConditioningCond clearanceImage: ConditioningMaximum permissible axle load, frontKgMaximum permissible axle load, rearKgMaximum permissible axle load, rearKg			6-pillars
Seat Max-Professional Plus, pneumatic suspension and swivelImage: seat state	·		•
Passenger seatImage: seatAdvance digital displayImage: seatAdvance digital displayImage: seatLED working lightsImage: seatLED driving lightImage: seatOMENSIONS AND WEIGHTSFront tyres (min.)Rear tyres (min.)Image: seatRear tyres (min.)Image: seatWheebaseImage: seatUmage: seatImage: seatHeight (max.)Image: seatWidth (max.)Image: seatGround clearanceImage: seatTotal unladen weightKgMaximum permissible axle load, frontKgMaximum permissible axle load, frontKg			•
Advance digital displayImage: constraint of the second	· · ·		
LED working lightsImage: meta-science science			
LED driving lightImage: constraint of the second secon			•
DIMENSIONS AND WEIGHTSFront tyres (min.)Gold 600/65 R34"Rear tyres (min.)T10/70 R38"Wheelbasemm3120Length (min.)mm4910Height (max.)mm3436Width (max.)mm2751Ground clearancemm600Total unladen weightKg9440Maximum permissible axle load, frontKg10000			
Front tyres (min.)Image: Constant of the section of the			
Rear tyres (min.)Imm710/70 R38"Wheelbasemm3120Length (min.)mm4910Height (max.)mm3436Width (max.)mm2751Ground clearancemm600Total unladen weightKg9440Maximum permissible axle load, frontKg6500Maximum permissible axle load, rearKg10000	Front tyres (min.)		600/65 R34"
Wheelbasemm3120Length (min.)mm4910Height (max.)mm3436Width (max.)mm2751Ground clearancemm600Total unladen weightKg9440Maximum permissible axle load, frontKg6500Maximum permissible axle load, rearKg10000			710/70 R38"
Height (max.)mm3436Width (max.)mm2751Ground clearancemm600Total unladen weightKg9440Maximum permissible axle load, frontKg6500Maximum permissible axle load, rearKg10000		mm	3120
Width (max.)mm2751Ground clearancemm600Total unladen weightKg9440Maximum permissible axle load, frontKg6500Maximum permissible axle load, rearKg10000		mm	
Ground clearancemm600Total unladen weightKg9440Maximum permissible axle load, frontKg6500Maximum permissible axle load, rearKg10000		mm	
Total unladen weightKg9440Maximum permissible axle load, frontKg6500Maximum permissible axle load, rearKg10000			
Maximum permissible axle load, front Kg 6500 Maximum permissible axle load, rear Kg 10000			
Maximum permissible axle load, rear Kg 10000	-		
· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·		
ruxingir permissione weight Ng 14000	•		
		Ng	14000

• = standard \bigcirc = optional - = not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.