

# AGGROFARM S SERIES



5075 // 5095 // 5105 // 5105 HD  
5115 // 5125

STAGE IIIB EPA  
STAGE IV EPA



**DEUTZ  
FAHR**

TECHNICAL DATA		AGROFARM					
		5075	5095	5105	5105 HD	5115	5125
<b>ENGINE</b>							
Type		FARMotion					
Emission level		EPA - Stage IIIB		EPA - Stage IV			
Cylinders/Displacement	n°/cc	4/3849					
Bore/Stroke	mm	103/115.5					
Aspiration		Turbo Intercooler					
Injection @ pressure	Type	Common Rail @ 2,000 bar					
Max. power @ 2000 rpm	kW/HP	55.4/75	71/97	78/106	85/116	93/126	
Rated power @ 2200 rpm	kW/HP	55.4/75	57.3/92	74/101	80,6/110	88/120	
Max. torque @ 1600 rpm	Nm	353	386	425	462	508	
Torque rise	%	47		32		31	
Visco cooling fan		●					
Fuel tank/AdBlue	l	145/-		145/10			
EAT	System	DOC		SCR			
<b>TRANSMISSION</b>							
SDF transmission	Type	T4330		T4350	T5350		
Gearbox	n°	5 gears x 2 or 4 ranges					
<b>HYDRAULIC SHUTTLE</b>							
PowerShuttle	Type	Hydraulic with lever under steering wheel					
Adjust. response of PowerShuttle		5 different setting					
N° of speed with Hi-Lo (2 ranges)	n°	20+20 Hi-Lo					
N° of speed with Hi-Lo (4 ranges)	n°	40+40 Hi-Lo					
Stop&Go		●					
ComfortClutch		●					
<b>PTO</b>							
Electrohydraulic engagement				●			
540/540ECO			●			-	
540/540ECO/1000/1000ECO			-			●	
<b>LIFT</b>							
Mechanical rear lift			●			-	
Mechanical rear lift with EasyLift			○			-	
Electronic rear lift			-			●	
Rear lifting capacity (STD)	Kg	3600					
Rear lifting capacity (OPT)	Kg	4525			5410		
<b>HYDRAULICS</b>							
Pump flow	l/min	55					
Rear spool valves	n°	2/3			3		
<b>BRAKES</b>							
4 wheel braking				●			
Mechanical parking brake				●			
Hydraulic trailer brake				○			
<b>FRONT AXLE</b>							
Front axle	Size	1.5			2		
Steering angle	degrees	50			55		
Electrohydraulic 4WD engagement				●			
Electrohydraulic Diff. Lock engagement				●			
<b>CAB</b>							
4 pillar cab				●			
High visibility roof - FOOPS				●			
Hydro Silent-Block suspension				●			
Manual A/C				●			
Pneumatic suspended seat		●				-	
DELUXE pneum. suspended seat		○				●	
Passenger seat		○				●	
External controls for PTO and lift				●			
Radio				●			
<b>DIMENSIONS AND WEIGHTS</b>							
Wheelbase	mm	2400					
Max. length	mm	4268					
Centre rear axle-cab	mm	1968					
Weight	Kg	3900	4000	4250	4350		
Front admissible load	Kg		2900	3000	3000		
Rear admissible load	Kg		3700	4000	5000		
Total admissible load	Kg		6500	7000	7500		

● = standard ○ = optional - = not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.