

SERIES

4 - 4E

AGGROFARM



4075 // 4090.4 // 4100.4

STAGE I

4065 E // 4075 E // 4085 E

4080.4 E // 4090.4 E // 4100.4 E

STAGE III A



**DEUTZ
FAHR**

TECHNICAL DATA	AGROFARM 4			
		4075	4090.4	4100.4
ENGINE				
Model		SDF 1000.3 WTI	SDF 1000.4 WTI	
Emission level			Stage I	
Cylinder/Displacement	n°/cc	3/3000	4/4000	
Electronic governor		-	●	
Turbocharged			-	
Turbo Intercooler			●	
Max. power (2000/25/EC)	kW/HP	53/72	62.5/85	70/95
Max. torque	Nm	265	348	373
Fuel tank capacity	l		70	
TRANSMISSION				
Synchronized transmission			●	
Mechanical shuttle (on steering column)			●	
Number of speeds	n°		30+15	
Minimum speed (2WD/4WD)	km/h	0.18/0.23	-/0.23	
Maximum speed (2WD/4WD)	km/h	30/40	-/40	
PTO				
Mechanical engagement			●	
540/540ECO			●	
Groundspeed PTO			●	
AXLES AND BRAKES				
2WD front axle		○	-	
4WD front axle with brakes			●	
Front wheel drive mechanically engaged			●	
Mechanically operated front and rear differential lock			●	
Hydrostatic steering with independent pump			●	
Steering angle	degrees		55	
Final epicyclic reduction			●	
Oil-immersed disc brakes			●	
HYDRAULIC SYSTEM AND HITCH				
Category			II	
Open centre hydraulic system			●	
Fixed displacement pump delivery	l/min		42	
Auxiliary rear mechanical spool valves	n°	2	3	
Mechanically controlled rear lift			●	
EasyLift			●	
Rear lift capacity	kg		3500	
DRIVING POSITION				
Platform mounted on Silent-Block			○	
Cab with ventilation			○	
Cab with air conditioning			●	
Side mounted levers			●	
DIMENSIONS AND WEIGHTS				
Width (min.-max.)	mm		1773-1941	
Wheelbase (2WD/4WD)	mm	2041/1976	-/2106	
Total unladen weight platform version (2WD/4WD)	kg	2700/3000	-/3100	
Total unladen weight cab version (2WD/4WD)	kg	2850/3150	-/3250	
Maximum permissible total weight (2WD/4WD)	kg	3800/4800	-/4800	


TECHNICAL DATA	AGROFARM 4E					
	4065 E	4075 E	4085 E	4080.4 E	4090.4 E	4100.4 E
ENGINE						
Model		SDF 1000.3 WT	SDF 1000.3 WTI		SDF 1000.4 WTI	
Emission level			Stage III A			
Cylinder/Displacement	n°/cc	3/3000			4/4000	
Electronic governor			-		●	
Turbocharged		●			-	
Turbo Intercooler		-			●	
Max. power (2000/25/EC)	kW/HP	45.6/62	53/72	60.3/82	58.8/80	62.5/85
Max. torque	Nm	240	265	318	320	348
Fuel tank capacity	l				70	
TRANSMISSION						
Synchronized transmission				●		
Mechanical shuttle (on steering column)				●		
Number of speeds	n°				30+15	
Minimum speed (2WD/4WD)	km/h	0.18/0.23			-/0.23	
Maximum speed (2WD/4WD)	km/h	30/40			-/40	
PTO						
Mechanical engagement				●		
540/540ECO				●		
Groundspeed PTO				●		
AXLES AND BRAKES						
2WD front axle			○			-
4WD front axle with brakes				●		
Front wheel drive mechanically engaged				●		
Mechanically operated front and rear differential lock				●		
Hydrostatic steering with independent pump				●		
Steering angle	degrees				55	
Final epicyclic reduction				●		
Oil-immersed disc brakes				●		
HYDRAULIC SYSTEM AND HITCH						
Category					II	
Open centre hydraulic system				●		
Fixed displacement pump delivery	l/min				42	
Auxiliary rear mechanical spool valves	n°	2			3	
Mechanically controlled rear lift				●		
EasyLift				●		
Rear lift capacity	kg	2500			3500	
DRIVING POSITION						
Platform mounted on Silent-Block				○		
Cab with ventilation				○		
Cab with air conditioning		○			●	
Side mounted levers				●		
DIMENSIONS AND WEIGHTS						
Width (min.-max.)	mm	1785-1896				1773-1941
Wheelbase (2WD/4WD)	mm	2041/1976			2171/2106	-/2106
Total unladen weight platform version (2WD/4WD)	kg	2500/2800	2700/3000		2800/3100	-/3100
Total unladen weight cab version (2WD/4WD)	kg	2650/2950	2850/3150		2950/3250	-/3250
Maximum permissible total weight (2WD/4WD)	kg	3800/4800			-/4800	

● = standard ○ = option - = not available

Technical data and figures are only provided for guidance. DEUTZ-FAHR is committed to continuously adapting its products to your requirements and therefore reserves the right to make updates without prior notice.



Follow us on   

DEUTZ-FAHR is a brand of  SDF

To discover more please contact your dealer or visit deutz-fahr.com

Marketing-Communication Service – Code 308.9018.3.4-0 – 05/24

