

DEUTZ-FAHR  
4050 E - 4055 E  
4065 E - 4075 E - 4080 E




Technical sheet	4E Series					
	4050 E	4055 E	4065 E	4075 E	4080 E	
<b>ENGINE</b>						
Manufacturer		SDF 1000.3 WT	SDF 1000.3 WT	SDF1000.3WTI	SDF 1000.3WTI	SDF 1000.4WTI
Emissions		Stage 3A	Stage 3A	Stage 3A	Stage 3A	Stage 3A
Cylinder/Displacement	n°/cc	3/3000	3/3000	3/3000	3/3000	4/4000
Electronic governor		-	-	-	●	●
Turbocharged		●	●	-	-	-
Turbo intercooler		-	-	●	●	●
Max. power (2000/25/EC)	kW/HP	36.8/50	45.6/62	53/72	60.3/82	58.8/80
Maximum torque	Nm	213	240	265	318	320
Air filter with dust ejector		●	●	●	●	●
Cyclone pre-filter		○	○	○	○	○
Fuel tank capacity	l	65	65	65	65	65
<b>TRANSMISSION</b>						
Synchronized transmission		●	●	●	●	●
Mechanical shuttle (on steering column)		●	●	●	●	●
Number of speeds	n°	15+15	30+15	30+15	30+15	30+15
Minimum speed (2WD/4WD)	km/h	0.14/0.18	0.12/0.15	0.12/0.15	0.12/0.15	0.12/0.15
Maximum speed (2WD/4WD)	km/h	30/40	30/40	30/40	30/40	30/40
<b>PTO</b>						
Mechanical engagement		●	●	●	●	●
540/540ECO		●	●	●	●	●
Ground speed PTO		●	●	●	●	●
<b>AXLES AND BRAKES</b>						
2WD		○	○	○	○	○
4WD front axle with brakes		●	●	●	●	●
Front wheel drive mechanically engaged		●	●	●	●	●
Mechanically operated front and rear differential lock		●	●	●	●	●
Hydrostatic steering with independent pump		●	●	●	●	●
Steering angle	degrees	55	55	55	55	55
Final epicyclic reduction		●	●	●	●	●
Oil-immersed disc brakes		●	●	●	●	●
<b>HYDRAULIC SYSTEM AND HITCH</b>						
Category		II	II	II	II	II
Open centre hydraulic system		●	●	●	●	●
Fixed displacement pump delivery	l/min	42	42	42	42	42
Auxiliary rear mechanical spool valves	n°	2	2	2	2	3
Mechanically controlled rear lift		●	●	●	●	●
Easy lift		●	●	●	●	●
Rear lift capacity	kg	2500	2500	3490	3490	3490
<b>DRIVING POSITION</b>						
Platform mounted on Silent-Block		○	○	○	○	○
Cab with ventilation		○	○	○	○	○
Cab with air conditioning		-	○	●	●	●
Side mounted levers		●	●	●	●	●
<b>DIMENSIONS AND WEIGHTS</b>						
Width (min-max)	mm	1785-1896	1785-1896	1799-1941	1799-1941	1799-1941
Wheelbase (2WD/4WD)	mm	2041/1976	2041/1976	2041/1976	2041/1976	2171/2106
Total unladen weight platform version (2WD/4WD)	kg	2500/2800	2500/2800	2700/3000	2700/3000	2800/3100
Total unladen weight cab version (2WD/4WD)	kg	2650/2950	2650/2950	2700/3150	2700/3150	2950/3250
Maximum permissible total weight (2WD/4WD)	kg	3800/4800	3800/4800	3800/4800	3800/4800	3800/4800

● standard ○ optional - not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

DEALER

To discover more please contact your dealer or visit [deutz-fahr.com](http://deutz-fahr.com).

DEUTZ-FAHR is a brand of  SDF

